


NT50B01 SmartNIC with Link™ Capture Software

2x1/10G, 2x10/25G

DATA SHEET



Packet Capture and Replay

Use cutting-edge SmartNIC technology to add real-time line-rate performance to your application. The NT50B01 SmartNIC provides full packet capture of network data at 50 Gbps with zero packet loss. Nanosecond precision time-stamping and merge of packets from multiple ports ensures correct timing and sequencing of packets. The SmartNIC can also be used for 100% packet replay with nanosecond precision of all networking traffic for analytics, testing and simulation.

The NT50B01 SmartNIC enables full utilization of CPU cores through advanced receive side scaling with support for tunneling protocols, such as GTP, IP-in-IP, NVGRE and VXLAN. The NT50B01 SmartNIC can also remove duplicate packets, slice packets and filter packets to reduce the amount of data and thereby offload the server system and applications. Stateful flow processing with support for 50 million flows enables CPU-hungry applications, such as Suricata, to intelligently select exactly which flows to process and which to ignore. Flow records are maintained for all flows and reported to the application.

The NT50B01 SmartNIC is NEBS level 3 compliant.

Applications

Napatech SmartNICs enable implementation of high-performance network appliances based on standard servers. Examples of applications include:

- Quality of experience optimization
- Financial latency measurement
- Customer experience analysis
- Data loss prevention
- Cyber defense
- Fraud detection and compliance management
- Infrastructure management and security
- Network and application performance
- Troubleshooting and compliance



Wireshark



Suricata



n2disk



Snort



Zeek



TRex

FEATURE HIGHLIGHTS AND SPECIFICATIONS

Rx Packet Processing

- Zero packet loss for packet size 64 – 10,000 bytes
 - Sustained traffic up to 50 Gbps (PCIe3 x16 packet bandwidth)
 - Line rate 2 × 25 Gbps traffic burst, 1700 milliseconds buffering
- Multi-port packet merge, sequenced in time stamp order
- L2, L3 and L4 protocol classification
- GTP, IP-in-IP, GRE, NVGRE, VxLAN, Pseudowire, Fabric Path, VNtag tunneling support
- Pattern match, network port, protocol, length, and error filters
- Custom flow definitions based on 2-, 3-, 4-, 5- or 6-tuple
- Flow match/actions: Forward to application or network port or drop packet
- Stateful flow management(*)
 - 25 million bidirectional IPv4 or IPv6 flows
 - Learning rate: 2 million flows/sec
 - TCP flow termination, flow timeout, or application-requested
 - Flow records with Rx packet/byte counters and TCP flags
- Stateless flow management
 - Up to 36,000 IPv4 or up to 7,500 IPv6 2-tuple flows
- Custom hash keys, symmetric hash key option
- CPU load distribution based on hash key or filter or per flow
- 128 Rx queues, 16 MB – 1 TB Rx buffer size
- Packet descriptors with metadata
- IP fragment handling
- Deduplication
- Slicing at dynamic offset or fixed offset from start or end of packet
- Extended RMON1 and counters per filter and per queue

Tx Packet Processing

- Line rate Tx up to 100 Gbps for packet size 64 – 10,000 bytes
- Replay as captured with nanoseconds precision
- Per-port traffic shaping
- Port-to-port forwarding
- 128 Tx queues, 4 MB Tx buffer size

Time Stamping and Synchronization

- Rx time stamp and Tx time stamp inject
- OS time synchronization
- Time stamp formats: Unix 10 ns, Unix 1 ns, PCAP 1 us, PCAP 1 ns

Network Standards

- IEEE 802.3 1G, 10G and 25G Ethernet

Supported pluggable modules

- 100GBASE-T, SX, LX, ZX (*)
- 10GBASE-SR, CR, LR, ER
- 25GBASE-SR, LR, LR-BiDi

Software

- Operating systems: Linux
- libpcap and DPDK
- Napatech NTAPI for highest performance and advanced features
- SDK tools included in source code for debugging and prototyping and as application examples

Hardware

- Xilinx XCKU15P FPGA
- 10 GB DDR4 SDRAM
- PCIe Gen3 16 lanes @ 8 GT/s
- 2 × SFP28 network ports
- Flash memory with support for two boot images
- Built-in thermal protection
- Physical dimensions: ½-length and ½-height PCIe
- Weight excluding pluggable modules: 350 g
- MTBF according to UTE C 80-810: 991,182 hours
- Power consumption including 25GBASE-SR modules and typical traffic load: 30 Watts

Environment for NT50B01

- Operating temperature: –5 °C to 55 °C (23 °F to 131 °F) measured around the SmartNIC
- Operating humidity: 5% to 85%
- Altitude: < 1,800 m
- Airflow: >= 3.5 m/s

Regulatory Approvals and Compliances

- PCI-SIG®, NEBS level 3, CE, CB, RoHS, REACH, cURus (UL), FCC, ICES, VCCI, RCM

Orderable port speed configurations

Product	Data Rates included
NT50B01-2x25/10	2 × 10/25 Gbps
NT50B01-2x25/10/2x10/1(*)	2 × 10/25 Gbps and 2 × 1/10 Gbps

(*)Future release